

8-Gallon or Base-Mount

Air Compressor/
Generator Combinations

Single/Two Stage — Gasoline



AG2-SM14-08M1

Ideal for jobsites and work trucks, the air compressor/generator combination units go a long way to increasing productivity. Install a stationary unit in your service truck and you'll have everything you need to operate air tools and power electrical tools.

Compressor Pump:

Cast iron compressor pump | Splash lubricated | Stainless-steel braided discharge hose | Large canister intake filter | Oil level sight indicator

Generator:

Brushless alternator | Total harmonic distortion (THD) less than 5% | 100% copper windings | Comes standard with (2) 120V, 20A and (1) 240V, 20A receptacles (Two stage models)

Frame:

Powder coated 8-gallon twin tank receivers (Portable and stationary models) | 3/16-inch base plate to reduce vibration | 16-gauge powder coated two-piece belt guard | 13-inch flat-free tires (Two stage portable models) (10-inch on AG1-PH65-08M1)

Components:

Regulator and two gauges for tank and outlet pressure | Manual drain valves for proper maintenance | 12 or 16½-inch fly wheel | Quality pilot valve unloader



8-Gallon or Base-Mount

Air Compressor/Generator Combinations – Single/Two Stage – Gasoline

PORTABLE MODELS	ALTERNATOR WATTAGE										
	MODEL NUMBER	CFM @ 90 PSI	CFM @ PSI	MAX. AC OUTPUT	CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD	RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.
AG1-PH65-08M1	11.9	10.9 @ 125	1800 watts	600 watts	1600 watts	(2) NEMA 5-20R	196cc Honda GX200 OHV	Single stage	44.5x26x27.5in.	257 lb.	207 lb.
AG2-PH13-08M1	16.4	15.7 @ 175*	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	389cc Honda GX390 OHV	Two stage	52x28x34in.	450 lb.	375 lb.
AG2-PK14-08M1	16.4	15.7 @ 175*	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	429cc Kohler CH440 OHV	Two stage	52x28x34in.	450 lb.	375 lb.
AG2-PM14-08M1	16.4	15.7 @ 175*	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage	52x28x34in.	450 lb.	375 lb.

*Equipped with 150-PSI maximum rated regulator.

STATIONARY MODELS	ALTERNATOR WATTAGE										
	MODEL NUMBER	CFM @ 90 PSI	CFM @ 175 PSI*	MAX. AC OUTPUT	CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD	RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.
AG2-SH13-08M1	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	389cc Honda GX390 OHV	Two stage	44x22x34in.	465 lb.	365 lb.
AG2-SK14-08M1	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	429cc Kohler CH440 OHV	Two stage	44x22x34in.	465 lb.	365 lb.
AG2-SM14-08M1	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage	44x22x34in.	465 lb.	365 lb.

*Equipped with 150-PSI maximum rated regulator.

BASE-MOUNT MODELS	ALTERNATOR WATTAGE										
	MODEL NUMBER	CFM @ 90 PSI	CFM @ 175 PSI*	MAX. AC OUTPUT	CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD	RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.
AG2-SH13-B	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	389cc Honda GX390 OHV	Two stage	47x22x28in.	390 lb.	325 lb.
AG2-SK14-B	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	429cc Kohler CH440 OHV	Two stage	47x22x28in.	390 lb.	325 lb.
AG2-SM14-B	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage	47x22x28in.	390 lb.	325 lb.

*Equipped with 150-PSI maximum rated regulator.

Options:

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0019	Electric start - battery, box and cables not included - For easy starting	Two stage Honda models
AX-0028	Lifting hook - For easier portability	Two stage portable & stationary models
AX-0063	Lifting hook - For easier portability	Base-mount models
AX-0064*	Electric start - battery box and cables included, battery not included - For easy starting	Two stage Honda models
AX-0068	Idle down - When activated it automatically throttles down engine to conserve fuel, includes electric start - battery not included	Two stage Honda models
AX-0071	Electric start - battery, box and cables not included - For easy starting	Kohler models
AX-0072*	Electric start - battery box and cables included, battery not included - For easy starting	Kohler models
AX-0073	Electric start - battery, box and cables not included - For easy starting	Mi-T-M engine models
AX-0074*	Electric start - battery box and cables included, battery not included - For easy starting	Mi-T-M engine models
AX-0075	Idle down - See AX-0068 for description	Mi-T-M engine models
IX-0055	Remote start/choke - 6-ft. wire extension for key switch. You will also need to order electric start option, AX-0019 or idle down option, AX-0068.	Two stage Honda models
IX-0059	Remote start/choke - 6-ft. wire extension for key switch, sealed cable. You will also need to order electric start option, AX-0019 or idle down option, AX-0068.	Two stage Honda models

*Battery box cannot be mounted at the factory but can be shipped with the unit for custom mounting. Consult dealer for more information.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
70-0357	Engine oil drain extension - 14-inch flexible drain hose makes oil changes clean and easy	AG1-PH65-08M1
70-0358	Engine oil drain extension - 14-inch flexible drain hose makes oil changes clean and easy	Two stage models
854-0093	Service truck mount kit - Includes four rubber isolators to reduce wear. Recommended for models mounted in service truck applications	Two stage portable & stationary models
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	All models



NEMA 5-20R
125V



NEMA L6-20R
240V

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.