



WTP-F03-1MGME

**Components:**

Poly impellers with stainless-steel inserts can handle solid suspended particles up to 3/8-inch in diameter (WTP-F02-1MGM has nylon propellers) | Polypropylene housing suitable for corrosive environments | Self-priming capabilities with maximum suction lift up to 25-foot | EPDM mechanical seal and inlet valve for longevity and reliability

*These pumps give you the advantage of one of the highest outputs in the industry. Both the 2-inch and 3-inch pumps are designed for chemical and liquid fertilizer transfer to maximize uptime in the field and the polypropylene housing makes them suitable for corrosive environments.*

MODEL NUMBER	SUCTION DISCHARGE SIZE	MAXIMUM GPM	MAXIMUM PSI	MAXIMUM SUCTION LIFT	DISPLACEMENT/ENGINE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
WTP-F02-1MGM	2in.x2in.	200	58	Up to 25ft.	212cc Mi-T-M OHV	18.5x18.5x14in.	51 lb.	42 lb.
WTP-F03-1MGME	3in.x3in.	440	54	Up to 25ft.	420cc Mi-T-M OHV with electric start - battery not included	23.5x19.5x17.5in.	102 lb.	93 lb.

**Accessories:**

PART NUMBER	DESCRIPTION	FITS MODELS
15-0306	20-ft. x 2-in. PVC suction hose with poly C&E fittings	WTP-F02-1MGM
55-0054	2-in. poly male adapter F	WTP-F02-1MGM
55-1895	2-in. poly female adapter B	WTP-F02-1MGM
70-0550	2-in. replacement chemical pump seal kit	WTP-F02-1MGM
15-0307	20-ft. x 3-in. PVC suction hose with poly C&E fittings	WTP-F03-1MGME
55-2288	3-in. poly male adapter F	WTP-F03-1MGME
55-2289	3-in. poly female adapter B	WTP-F03-1MGME
70-0551	3-in. replacement chemical pump seal kit	WTP-F03-1MGME



3-inch pump accessories shown: 20-ft. x 3-in. PVC suction hose with poly C&E fittings, 15-0307; 3-in. poly male adapter F, 55-2288; and 3-in. poly female adapter B, 55-2289

 **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).