

with 510-Gallon Water Tank



MWT-0510-2MHD shown with
hard suction option, TX-0008



Great for dust control, parking lot cleaning and simply transporting water to remote locations, the dual-axle water trailer features a large capacity 510-gallon water tank to get the job done fast. It comes with rear spray, fire and garden hose hook-ups and hydrant fill capabilities.



Water Trailer

Water Transport Trailer

Tank:

510-gallon elliptical low profile 3/8-inch thick polyethylene | 16-inch manhole with 4-inch vent and sump pump

Central Manifold:

Easy-to-operate butterfly brass valves

Plumbing:

1 1/2-inch fire hose hook-up with 50-foot x 1 1/2-inch hose and fog nozzle | Break-away hydrant fill with 25-foot x 2 1/2-inch hose | Dual rear spray heads | Garden hose connector | Manifold discharge system | Water hammer prevention valve

Trailer:

DOT approved | 12-inch under-clearance at axle | 7,000-lb. side-mount crank jack | Dual leaf spring suspension | Rubber mounted sealed lights | Wire storage basket | Two safety chains with snap hooks

Semi-Trash Pump:

2-inch suction and discharge that handles solids up to 3/4-inch diameter | Heavy-duty powder coated wraparound frame with 1-inch steel tubing | Silicon carbide mechanical seals | Precision molded cast iron impeller and volute for reduced vibration and wear

| MODEL NUMBER | DISPLACEMENT/ENGINE | PUMP | HITCH | TIRES | AXLES | BED FRAME | DIMENSIONS (LxWxH) | TRAILER WT. (EMPTY) | TRAILER WT. (LOADED) |
|---------------|-----------------------|-----------------|------------|--------------------|--|-----------|------------------------|---------------------|----------------------|
| MWT-0510-2MHD | 118cc Honda GX120 OHV | 2in. semi-trash | 2in., ball | (4) ST225-75 15in. | (2) 3,500 lb. tandem with hydraulic surge brakes | 5ft.x8ft. | 13ft. 7in.x82in.x70in. | 1,580 lb. | 5,900 lb. |

Options:

| PART NUMBER | DESCRIPTION |
|-------------|---|
| TX-0008 | Hard suction option - Allows you to draw water from an auxiliary source (pond, water pit, etc.). The fire hose is designed to be used with pressurized water and lays flat for easy storage. |
| TX-0010 | Adjustable trailer coupler hitch - Replaces the standard 2-inch ball hitch with a 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket |
| TX-0019 | Lunette ring hitch - Replaces the standard 2-inch ball hitch with an 3-inch integrated lunette ring for use with pintle hitches |



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov